

Highly variable due to 25 base sizes  
with over 50,000 possible combinations

#### Dimensions

| W x H x D (mm)  | W x H x D (mm)  | W x H x D (mm)  |
|-----------------|-----------------|-----------------|
| 200 x 200 x 80  | 300 x 300 x 160 | 300 x 600 x 200 |
| 300 x 200 x 80  | 400 x 300 x 160 | 400 x 500 x 200 |
| 200 x 200 x 120 | 300 x 500 x 160 | 400 x 600 x 200 |
| 300 x 200 x 120 | 400 x 400 x 160 | 500 x 500 x 200 |
| 400 x 200 x 120 | 300 x 600 x 160 | 500 x 600 x 200 |
| 300 x 300 x 120 | 300 x 300 x 200 | 500 x 500 x 260 |
| 400 x 300 x 120 | 400 x 300 x 200 | 600 x 600 x 260 |
| 300 x 500 x 120 | 500 x 300 x 200 |                 |
| 300 x 600 x 120 | 400 x 400 x 200 |                 |



#### Technical data




|                          |   |
|--------------------------|---|
| Material                 | Stainless steel 1.4301 / 304  |
| Surface                  | grinded, grain 320  |
| Material thickness       | 1,25 mm   |
| Ingress protection       | screwed lid: IP66 / IP69<br>hinged lid: IP66                                    |
| Impact resistance        | screwed lid: IK09 to DIN EN 60068-2-75<br>hinged lid: IK08 to DIN EN 60068-2-75 |
| Temperature range        | -55 °C to +135 °C with silicone seal  |
| Other options on request | EMC, other temperature ranges, coating  |

#### Machining options

- Laser machining
- Stud welding
- Projection welding
- Laser marking
- Wet painting
- Powder coating
- Screen printing
- Pad printing
- Mounting:  
Assembly according to customer requirements  
or electronics assembly

Please contact us, our team will assist you!

ROSE Systemtechnik GmbH  
Erbeweg 13-15  
D-32457 Porta Westfalica  
Fon +49 571 50 41 0  
E-Mail rose@rose-pw.de



# Stainless Steel RMS

The ROSE Modular System



A Phoenix Mecano Company



## Enclosure Base

The new design of the enclosure base offers some decisive advantages:


- The integrated brackets in the lower part of the housing enables flexible positioning of electrical installations
- Two additional welding studs also provide the possibility to vertically mount the mounting rail
- Imprinted grounding signs mark 4 possible earthing points in the bracket
- For wall mounting and the installation of external mounting brackets you can find 4 mounting holes in the base of the enclosure



## Enclosure Lid

The modular design of the stainless steel housing envisages configuring the cover in a screwed or hinged version:

- Screwed variation with captive external hexagon screw M5
- Hinged version optionally with double ward 3 mm lock in stainless steel, plastic or zinc die-cast chrome-plated
- Grounding can be done via a grounding bolt M6x16mm
- Tested IP rating of IP66 for the hinged lid, IP69 for the screwed lid



### Seal

- Silicone seal, temperature range -55 °C to +135 °C
- Optional EMC seal
- Other seals on request

## Accessories

To complete the innovative ROSE Modular System, we offer you a wide range of accessories:

- 4 different flanges in the sizes 260 x 85 mm to 460 x 165 mm, material thickness 3 mm
- Mounting plate
- DIN rails
- Pole bracket
- External brackets, either screwed or welded, in a straight or cranked version

